NSN 5925-00-995-8373

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-995-8373

| Body Style: |
|--|
| Single pole type |
| Bushing Length: |
| 0.250 inches |
| Body Length: |
| 2.187 inches |
| Body Width: |
| 0.750 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 1.437 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.812 inches |
| Fragility Factor: |
| Moderately rugged |
| Mounting Surface To Terminal End Distance: |
| 2.234 inches |
| Pole Quantity: |
| 1 |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Storage Type: |
| General purpose warehouse |
| Thready Qty Per Inch (tpi): |
| 32 |
| Maximum Continuous Load Current Rating Per Pole: |
| 60.0 amperes ac single location and 60.0 amperes dc single location |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 120.0 ac single location and 30.0 dc single location |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 3500.0 ac single location and 6000.0 dc single location |
| Circuit Protection Type: |
| Overcurrent single location |
| Trip Release Method: |
| Thermal single location |
| Trip Release Characteristic: |
| Time delay single location |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 138.0 single location |
| Reset Method: |
| Manual |

NSN 5925-00-995-8373 Circuit Breaker - Page 2 of 2



| Main Contact Tripping Mechanism Type: |
|---|
| Trip free |
| Manual Actuator Type And Quantity: |
| 1 push button |
| Actuator Function: |
| Reset |
| Actuator Position Designation: |
| At pole one |
| Internal Trip Release Configuration: |
| Series trip single location |
| Thread Size: |
| 0.138 inches |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 25.000 at 200 pct single location and 60.000 at 200 pct single location |
| Inclosure Protection Type For Which Designed: |
| Explosion proof and fungus proof |
| Trip Release Ambient Tempurature Rating: |
| 25.0 degrees celsius single location |
| Frequency In Hertz: |
| 60.0 single location |
| Unpackaged Unit Weight: |
| 0.240 pounds |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 2 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |
| |