NSN 5925-00-996-5183

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-996-5183

Overall Length:
2.000 inches
Overall Height:
3.296 inches
Overall Width:
0.850 inches
Case Material:
Metal
Pole Quantity:
3
Arc Quenching Method:
Deion
Mounting Facility Type And Quantity:
1 threaded bushing
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
1.5 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
120.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
145.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.469 inches
Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct all locations and 35.000 at 200 pct all locations

NSN 5925-00-996-5183

Circuit Breaker - Page 2 of 2



Inclosure Protection Type For Which Designed:
Explosion proof
Frequency In Hertz:
400.0 all locations
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fila:

A030a0