

View Online at <https://aerobasegroup.com/nsn/5925-00-998-8511>

Body Style:

Multipole-single actuator type

Bushing Length:

0.469 inches

Body Length:

0.750 inches

Body Width:

2.188 inches

Body Height:

2.188 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.594 inches

Center To Center Distance Between Terminals Parallel To Width:

0.188 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac all locations and 7.5 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations and 30.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations and 4000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

40.000 at 200 pct all locations and 100.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Explosion proof

Trip Release Ambient Temperature Rating:

77.0 degrees fahrenheit all locations

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

2.000 ounces

Test Data Document:

11871-7260-804-3 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0