NSN 5925-01-004-2474

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-004-2474

Body	Length:
------	---------

- 3.000 inches
- **Body Width:**
- 1.478 inches
- **Body Height:**
- 2.300 inches
- **Case Material:**
- Plastic
- Center To Center Distance Between Terminals Parallel To Width:
- 1.740 inches
- **Boss Height:**
- 0.188 inches
- Pole Quantity:
- 2
- Mounting Facility Type And Quantity:
- 4 terminal
- Storage Type:
- General purpose warehouse
- Maximum Continuous Load Current Rating Per Pole:
- 50.0 amperes ac all locations
- **Operating Voltage Type And Rating Per Pole In Volts:**
- 240.0 ac all locations
- Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
- 10000.0 ac all locations
- **Circuit Protection Type:**
- Overcurrent all locations
- **Trip Release Method:**
- Thermal-magnetic all locations
- **Trip Release Characteristic:**
- Instantaneous all locations and time delay all locations
- Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
- 125.0 all locations
- **Reset Method:**
- Manual
- Main Contact Tripping Mechanism Type:
- Trip free
- Manual Actuator Type And Quantity:
- 2 toggle
- **Actuator Function:**
- Trip-reset
- **Actuator Position Designation:**
- At each pole

NSN 5925-01-004-2474

Circuit Breaker - Page 2 of 2



External Actuator Linkage Arrangement:

One and two linked

Trip Delay Time In Seconds Per Rated Continuous Current:

240.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

2 clip and 2 compression

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0