

View Online at <https://aerobasegroup.com/nsn/5925-01-004-9293>

Body Style:

Single pole type

Body Length:

2.000 inches

Body Width:

0.920 inches

Body Height:

1.545 inches

Case Material:

Plastic

Boss Height:

0.125 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 clip

Maximum Continuous Load Current Rating Per Pole:

2.5 amperes ac single location and 2.5 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 32.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location and 1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

0.050 at 200 pct single location and 1.000 at 200 pct single location

Special Features:

Handle equipped with internally mtg light emitting diode

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0