## NSN 5925-01-009-8976

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-009-8976

| Thread Pitch Diameters:   |
|---|
| +0.3503/+0.3537 inches  |
| Body Style:   |
| Multipole-single actuator type  |
| Bushing Length:   |
| 0.380 inches  |
| Body Length:  |
| 1.500 inches  |
| Body Width:   |
| 1.875 inches  |
| Case Material:  |
| Metal   |
| Center To Center Distance Between Terminals Parallel To Length:         |
| Between 0.844 inches and 0.906 inches                                   |
| Center To Center Distance Between Terminals Parallel To Width:          |
| Between 0.594 inches and 0.656 inches                                   |
| Fragility Factor:   |
| Moderately rugged   |
| Mounting Surface To Terminal End Distance:                              |
| 1.780 inches  |
| Pole Quantity:  |
| 3   |
| Arc Quenching Method:   |
| Magnetic blowout  |
| Mounting Facility Type And Quantity:                                    |
| 1 threaded bushing w/panel seal   |
| Storage Type:   |
| General purpose warehouse   |
| Special Handling Feature:   |
| Magnetic  |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Maximum Continuous Load Current Rating Per Pole:                        |
| 1.75 amperes ac all locations and 1.75 amperes dc all locations         |
| Operating Voltage Type And Rating Per Pole In Volts:                    |
| 250.0 ac all locations and 50.0 dc all locations                        |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 1000.0 ac all locations and 1000.0 dc all locations                     |
| Circuit Protection Type:  |
| Overcurrent all locations   |
| Trip Release Method:  |
| Magnetic all locations  |

## **NSN 5925-01-009-8976** Circuit Breaker - Page 2 of 2



| Trip Release Characteristic:   |
|--|
| Time delay all locations   |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 115.0 all locations  |
| Reset Method:  |
| Manual   |
| Main Contact Tripping Mechanism Type:                                  |
| Trip free  |
| Manual Actuator Type And Quantity:                                     |
| 1 toggle   |
| Actuator Function:   |
| Trip-reset   |
| Actuator Position Designation:   |
| At pole two  |
| Internal Trip Release Configuration:                                   |
| Series trip all locations  |
| Thread Size:   |
| 0.375 inches   |
| Trip Delay Time In Seconds Per Rated Continuous Current:               |
| 0.090 at 200 pct all locations and 0.600 at 200 pct all locations      |
| Inclosure Protection Type For Which Designed:                          |
| Hermetically sealed and shock resistant and vibration resistant        |
| Frequency In Hertz:  |
| 400.0 all locations  |
| Unpackaged Unit Weight:  |
| 6.300 ounces   |
| Thread Series Designator:  |
| Unef   |
| Terminal Type And Quantity:  |
| 6 wire hook  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A030a0   |
|  |