

View Online at <https://aerobasegroup.com/nsn/5925-01-010-2925>

**Body Style:**

Single pole type

**Body Length:**

2.300 inches

**Body Width:**

0.750 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.680 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.810 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Boss Height:**

0.115 inches

**Mounting Surface To Terminal End Distance:**

2.635 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.138 inches

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.150 at 200 pct single location and 0.600 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Corrosion resistant and fungus resistant

**Switch Terminal Type:**

Tab, solder lug

**Switch Current Rating And Type In Amps:**

5.0 ac and 1.0 dc

**Switch Voltage Rating And Type In Volts:**

125.0 ac and 60.0 dc

**Frequency In Hertz:**

60.0 single location

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0