

View Online at <https://aerobasegroup.com/nsn/5925-01-010-8921>

Overall Length:

6.120 inches

Overall Height:

3.920 inches

Overall Width:

4.950 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.214 inches and 0.228 inches

Switch Contact Arrangement:

Single pole, double throw

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

275.0 amperes ac all locations and 275.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

200.0 ac all locations and 28.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Relay trip all locations

Switch Location And Position Designation:

Internal at pole three

Inclosure Protection Type For Which Designed:

Corrosion resistant and humidity resistant and moisture resistant and fungus resistant

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Switch Current Rating And Type In Amps:

7.5 ac

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

4.500 pounds

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A030a0