

View Online at <https://aerobasegroup.com/nsn/5925-01-010-8921>

**Overall Length:**

6.120 inches

**Overall Height:**

3.920 inches

**Overall Width:**

4.950 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.214 inches and 0.228 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

275.0 amperes ac all locations and 275.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

200.0 ac all locations and 28.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Relay trip all locations

**Switch Location And Position Designation:**

Internal at pole three

**Inclosure Protection Type For Which Designed:**

Corrosion resistant and humidity resistant and moisture resistant and fungus resistant

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Switch Current Rating And Type In Amps:**

7.5 ac

**Frequency In Hertz:**

400.0 all locations

**Unpackaged Unit Weight:**

4.500 pounds

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A030a0