

View Online at <https://aerobasegroup.com/nsn/5925-01-011-2202>

Body Style:

Single pole type

Bushing Length:

0.250 inches

Body Length:

1.828 inches

Body Width:

0.906 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.625 inches

Mounting Surface To Terminal End Distance:

1.562 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

2.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

28.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

400.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Ultimate Trip Time Per Pole In Seconds:

1.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 125 pct all locations

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0