

View Online at <https://aerobasegroup.com/nsn/5925-01-011-7992>

**Body Style:**

Single pole type

**Bushing Length:**

0.250 inches

**Body Length:**

1.187 inches

**Body Width:**

0.750 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

0.650 inches

**Mounting Surface To Terminal End Distance:**

1.812 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

28.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

420.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

110.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

3.000 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.469 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

15.000 at 120 pct single location

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0