

View Online at <https://aerobasegroup.com/nsn/5925-01-014-4777>

**Body Style:**

Multipole-multiple actuator type

**Bushing Length:**

Between 0.146 inches and 0.166 inches

**Body Length:**

Between 2.490 inches and 2.510 inches

**Body Width:**

Between 1.510 inches and 1.530 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.180 inches and 1.200 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.740 inches and 0.760 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.802 inches and 1.822 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.740 inches and 0.760 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

Between 1.990 inches and 2.010 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

40.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

28.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One and two linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

18.000 at 200 pct all locations and 55.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Dustproof and fungus proof

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0