# NSN 5925-01-014-9857

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-014-9857

#### **Body Style:**

Multipole-single actuator type

## **Body Length:**

10.125 inches

## Body Width:

5.000 inches

#### **Body Height:**

4.062 inches

#### **Case Material:**

Plastic

## Center To Center Distance Between Terminals Parallel To Length:

## 8.875 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.719 inches

**Unthreaded Mounting Hole Diameter:** 

## 0.125 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.438 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.719 inches

## Boss Height:

0.250 inches

## Pole Quantity:

2

## Mounting Facility Type And Quantity:

4 unthreaded hole

## Storage Type:

General purpose warehouse

## Features Provided:

Adjustable trip release

## Maximum Continuous Load Current Rating Per Pole:

125.0 amperes ac all locations and 125.0 amperes dc all locations

## Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22000.0 ac all locations and 10000.0 dc all locations

## Circuit Protection Type:

Overcurrent all locations

## Trip Release Method:

Thermal-magnetic all locations

## Trip Release Characteristic:

Instantaneous all locations and time delay all locations

# NSN 5925-01-014-9857

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 all locations

#### **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

**Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

Between pole one and two

## Adjustable Trip Setting Current Range Per Pole In Amps:

+625.0/+1250.0 ac all locations and +625.0/+1250.0 dc all locations

## Trip Delay Time In Seconds Per Rated Continuous Current:

500.000 at 200 pct all locations

## Inclosure Protection Type For Which Designed:

General purpose

#### **Trip Release Ambient Tempurature Rating:**

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

## **Terminal Type And Quantity:**

4 compression

Shelf Life:

N/a

## Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0