## NSN 5925-01-019-0980

Circuit Breaker - Page 1 of 2

140.0 all locations



View Online at https://aerobasegroup.com/nsn/5925-01-019-0980

**Body Style:** Multipole-multiple actuator type **Body Length:** 2.189 inches **Body Width:** 2.560 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** Between 1.160 inches and 1.220 inches **Center To Center Distance Between Terminals Parallel To Width:** Between 0.740 inches and 0.760 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** Between 1.800 inches and 1.820 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.740 inches and 0.760 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 2.900 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 6 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

## **NSN 5925-01-019-0980** Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
11.000 at 200 pct all locations and 65.000 at 200 pct all locations
nclosure Protection Type For Which Designed:
Vibration resistant and shock resistant and fungus resistant and corrosion resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
0.650 pounds
Thread Series Designator:
Jnc
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
4030a0