

View Online at <https://aerobasegroup.com/nsn/5925-01-019-0981>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.189 inches

**Body Width:**

2.560 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.160 inches and 1.200 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.740 inches and 0.760 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.800 inches and 1.820 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.740 inches and 0.760 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

2.900 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

6000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

140.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

11.000 at 200 pct all locations and 65.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Vibration resistant and shock resistant and fungus resistant and corrosion resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Unpackaged Unit Weight:**

0.650 pounds

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0