

View Online at <https://aerobasegroup.com/nsn/5925-01-019-9696>

Body Style:

Single pole type

Mounting Slot Width:

0.164 inches

Body Length:

3.219 inches

Body Width:

1.469 inches

Body Height:

2.640 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

2.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.312 inches

Boss Height:

0.125 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 slot

Maximum Continuous Load Current Rating Per Pole:

4.75 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

105.000 single location and 150.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Relay trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

175.000 at 125 pct single location and 600.000 at 125 pct single location and 100.000 at 150 pct single location and 300.000 at 150 pct single location and 40.000 at 200 pct single location and 140.000 at 200 pct single location and 20.000 at 300 pct single location and 50.000 at 300 pct single location and 6.500 at 400 pct single location and 10.750 at 400 pct single location and 4.000 at 500 pct single location and 10.000 at 500 pct single location and 0.030 at 1000 pct single location and 0.080 at 1000 pct single location

Special Features:

Shock/vibration resistant 15 g shock, 10 g vibration

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

1 threaded stud and 2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0