

View Online at <https://aerobasegroup.com/nsn/5925-01-019-9696>

**Body Style:**

Single pole type

**Mounting Slot Width:**

0.164 inches

**Body Length:**

3.219 inches

**Body Width:**

1.469 inches

**Body Height:**

2.640 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

2.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.312 inches

**Boss Height:**

0.125 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 slot

**Maximum Continuous Load Current Rating Per Pole:**

4.75 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1500.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

105.000 single location and 150.000 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Relay trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

175.000 at 125 pct single location and 600.000 at 125 pct single location and 100.000 at 150 pct single location and 300.000 at 150 pct single location and 40.000 at 200 pct single location and 140.000 at 200 pct single location and 20.000 at 300 pct single location and 50.000 at 300 pct single location and 6.500 at 400 pct single location and 10.750 at 400 pct single location and 4.000 at 500 pct single location and 10.000 at 500 pct single location and 0.030 at 1000 pct single location and 0.080 at 1000 pct single location

**Special Features:**

Shock/vibration resistant 15 g shock, 10 g vibration

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

1 threaded stud and 2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0