NSN 5925-01-020-2470



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-020-2470 **Body Style:** Multipole-single actuator type **Mounting Slot Width:** 0.156 inches **Body Length:** 3.719 inches **Body Width:** 2.000 inches **Body Height:** 2.562 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Boss Height:** 0.187 inches **Pole Quantity:** 2 **Mounting Facility Type And Quantity:** 2 slot **Storage Type:** General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:**

Manual Actuator Type And Quantity: 2 toggle

Trip free

NSN 5925-01-020-2470 Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
2 bus bar and 2 compression
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A030a0