

View Online at <https://aerobasegroup.com/nsn/5925-01-022-5086>

**Body Style:**

Multipole-single actuator type

**Body Length:**

6.500 inches

**Body Width:**

4.125 inches

**Body Height:**

3.875 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

3.938 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.343 inches

**Unthreaded Mounting Hole Diameter:**

0.312 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.312 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.343 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.187 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Deion

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

100.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

135.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+1200.0/+1400.0 ac all locations

**Internal Trip Release Configuration:**

Series trip all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Frequency In Hertz:**

400.0 all locations

**Unpackaged Unit Weight:**

5.500 pounds

**Terminal Type And Quantity:**

6 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0