

View Online at <https://aerobasegroup.com/nsn/5925-01-022-6514>

Body Style:

Single pole type

Body Length:

6.000 inches

Body Width:

1.500 inches

Body Height:

3.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.125 inches

Unthreaded Mounting Hole Diameter:

0.172 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.125 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

75000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.009 at 200 pct single location and 0.020 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0