

View Online at <https://aerobasegroup.com/nsn/5925-01-022-8122>

**Body Style:**

Multipole-single actuator type

**Body Length:**

6.312 inches

**Body Width:**

2.750 inches

**Body Height:**

3.140 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

4.620 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.380 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.620 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.375 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.710 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

55.314 cubic inches

**Maximum Continuous Load Current Rating Per Pole:**

40.0 amperes ac all locations and 40.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

18000.0 ac all locations and 10000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Trip Delay Time In Seconds Per Rated Continuous Current:**

725.000 at 100 pct all locations and 1000.000 at 100 pct all locations and 30.000 at 200 pct all locations and 125.000 at 200 pct all locations and 15.000 at 250 pct all locations and 60.000 at 250 pct all locations and 9.000 at 300 pct all locations and 37.500 at 300 pct all locations and 4.250 at 400 pct all locations and 18.000 at 400 pct all locations and 2.400 at 500 pct all locations and 12.000 at 500 pct all locations and 0.440 at 1000 pct all locations and 2.400 at 1000 pct all locations and 0.590 at 2000 pct all locations

**Trip Release Ambient Temperature Rating:**

10.0 degrees celsius all locations and 50.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0