## NSN 5925-01-023-1410

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-023-1410 **Body Style:** Single pole type **Bushing Length:** 0.380 inches **Body Length:** 1.500 inches **Body Width:** 0.625 inches **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** 0.875 inches **Mounting Surface To Terminal End Distance:** 1.605 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** 

Trip-reset

## NSN 5925-01-023-1410

Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole one
nternal Trip Release Configuration:
Series trip single location
Thread Size:
0.375 inches
nclosure Protection Type For Which Designed:
Hermetically sealed
Frequency In Hertz:
60.0 single location
Thread Series Designator:
Jnef
Terminal Type And Quantity:
2 wire hook
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A030a0