NSN 5925-01-023-9116

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-023-9116 **Body Style:** Multipole-single actuator type **Body Length:** 6.438 inches **Body Width:** 4.938 inches **Body Height:** 3.157 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: 5.188** inches **Center To Center Distance Between Terminals Parallel To Width:** 1.500 inches **Unthreaded Mounting Hole Diameter:** 0.190 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Boss Height:** 0.250 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 125.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:**

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

NSN 5925-01-023-9116Circuit Breaker - Page 2 of 2



| Reset Method: |
|---|
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 1 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At pole two |
| Inclosure Protection Type For Which Designed: |
| General purpose |
| Trip Release Ambient Tempurature Rating: |
| 40.0 degrees celsius all locations |
| Frequency In Hertz: |
| 60.0 all locations |
| Terminal Type And Quantity: |
| 6 compression |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |