# NSN 5925-01-024-3345

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-024-3345

#### Body Style:

Multipole-multiple actuator type

#### **Body Length:**

2.500 inches

# Body Width:

1.500 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

1.938 inches

#### Center To Center Distance Between Terminals Parallel To Width:

#### 0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 2.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

# 0.750 inches

Fragility Factor:

Moderately rugged

#### **Boss Height:**

0.140 inches

#### Mounting Surface To Terminal End Distance:

Between 2.409 inches and 2.533 inches

#### Pole Quantity:

2

# Arc Quenching Method:

Magnetic blowout

# Mounting Facility Type And Quantity:

4 threaded hole

# Storage Type:

General purpose warehouse

# Special Handling Feature:

Magnetic

# Thready Qty Per Inch (tpi):

32

#### Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac all locations

### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

# **NSN 5925-01-024-3345** Circuit Breaker - Page 2 of 2



Trip Release Metho	od:
Magnetic-hydraulic all locations	
Trip Release Chara	acteristic:
Instantaneous all lo	cations
Ultimate Trip Ratin	ng Of Continuous Current Rating Per Pole In Percent:
125.0 all locations	
Reset Method:	
Manual	
Main Contact Tripp	ping Mechanism Type:
Trip free	
Manual Actuator T	ype And Quantity:
2 toggle	
Actuator Function	:
Trip-reset	
Actuator Position	Designation:
At each pole	
External Actuator	Linkage Arrangement:
One and two linked	
Internal Trip Relea	se Configuration:
Series trip all location	ons
Thread Size:	
0.138 inches	
Inclosure Protection	on Type For Which Designed:
Fungus resistant an	d moisture resistant
Frequency In Hertz	2:
60.0 all locations	
Unpackaged Unit \	Neight:
0.547 pounds	
Thread Series Des	ignator:
Unc	
Terminal Type And	I Quantity:
4 threaded stud	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A030a0	