

View Online at <https://aerobasegroup.com/nsn/5925-01-024-7367>

Body Style:

Single pole type

Bushing Length:

0.250 inches

Body Length:

2.189 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.812 inches

Mounting Surface To Terminal End Distance:

2.000 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac single location and 25.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3500.0 ac single location and 6000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 55.000 at 200 pct single location

Inclsure Protection Type For Which Designed:

Shockproof and vibrationproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Unpackaged Unit Weight:

2.500 ounces

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0