

View Online at <https://aerobasegroup.com/nsn/5925-01-024-9131>

Body Style:

Multipole-single actuator type

Body Length:

6.000 inches

Body Width:

4.500 inches

Body Height:

3.625 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.250 inches

Center To Center Distance Between Terminals Parallel To Width:

1.500 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.594 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Boss Height:

0.219 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

58.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct all locations and 6.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0