NSN 5925-01-024-9132



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-024-9132 **Body Style:** Multipole-single actuator type **Body Length:** 6.000 inches **Body Width:** 4.500 inches **Body Height:** 3.625 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:**

5.250 inches

Center To Center Distance Between Terminals Parallel To Width:

1.500 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.594 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.219 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

56.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

NSN 5925-01-024-9132 Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct all locations and 6.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
2.400 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0