NSN 5925-01-025-7001

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-025-7001

Body Style:
Multipole-single actuator type
Body Length:
4.125 inches
Body Width:
3.344 inches
Body Height:
4.125 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
2.625 inches
Center To Center Distance Between Terminals Parallel To Width:
1.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.125 inches
Boss Height:
0.125 inches
Pole Quantity:
3
3 Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 2 threaded hole
Mounting Facility Type And Quantity: 2 threaded hole Storage Type:
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature:
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi):
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole:
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts:
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations and 10000.0 dc all locations
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations and 10000.0 dc all locations Circuit Protection Type:
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations and 10000.0 dc all locations Circuit Protection Type: Overcurrent all locations

Time delay all locations

NSN 5925-01-025-7001

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Thread Size:
0.190 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
10.000 at 200 pct all locations and 200.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Thread Series Designator:
Unf
Terminal Type And Quantity:
6 clip
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filig:
A030a0