

View Online at <https://aerobasegroup.com/nsn/5925-01-026-5114>

Body Style:

Multipole-single actuator type

Body Length:

6.3125 inches

Body Width:

2.750 inches

Body Height:

3.1875 inches

Case Material:

Plastic

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.87501 inches

Boss Height:

0.90625 inches

Pole Quantity:

2

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 125.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations and 5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Trip Delay Time In Seconds Per Rated Continuous Current:

80.000 at 200 pct all locations and 325.000 at 200 pct all locations and 30.000 at 300 pct all locations and 130.000 at 300 pct all locations and 13.000 at 400 pct all locations and 70.000 at 400 pct all locations and 7.000 at 500 pct all locations and 45.000 at 500 pct all locations and 13.000 at 1000 pct all locations and 3.500 at 2000 pct all locations

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Special Features:

With line and load lugs

Frequency In Hertz:

60.0 all locations

Supplementary Features:

Operating voltage type and rating per pole in volts 250.0 dc in addition to cprf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0