

View Online at <https://aerobasegroup.com/nsn/5925-01-026-5114>

**Body Style:**

Multipole-single actuator type

**Body Length:**

6.3125 inches

**Body Width:**

2.750 inches

**Body Height:**

3.1875 inches

**Case Material:**

Plastic

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.87501 inches

**Boss Height:**

0.90625 inches

**Pole Quantity:**

2

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 125.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac all locations and 5000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Reset

**Trip Delay Time In Seconds Per Rated Continuous Current:**

80.000 at 200 pct all locations and 325.000 at 200 pct all locations and 30.000 at 300 pct all locations and 130.000 at 300 pct all locations and 13.000 at 400 pct all locations and 70.000 at 400 pct all locations and 7.000 at 500 pct all locations and 45.000 at 500 pct all locations and 13.000 at 1000 pct all locations and 3.500 at 2000 pct all locations

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Special Features:**

With line and load lugs

**Frequency In Hertz:**

60.0 all locations

**Supplementary Features:**

Operating voltage type and rating per pole in volts 250.0 dc in addition to cprf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0