NSN 5925-01-028-0806

Circuit Breaker - Page 1 of 2

Time delay all locations



View Online at https://aerobasegroup.com/nsn/5925-01-028-0806

Thread Pitch Diameters:
+0.3503/+0.3537 inches
Body Style:
Multipole-single actuator type
Bushing Length:
0.380 inches
Body Length:
1.562 inches
Body Width:
1.937 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.875 inches
Center To Center Distance Between Terminals Parallel To Width:
0.625 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.780 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
500.0 milliamperes ac third location
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:

NSN 5925-01-028-0806 Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.070 at 200 pct all locations and 0.700 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Hermetically sealed and shockproof and vibrationproof
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Unpackaged Unit Weight:
5.400 ounces
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0