## NSN 5925-01-028-2782

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-028-2782

Body Style:
Multipole-single actuator type
Bushing Length:
0.675 inches
Body Length:
1.562 inches
Body Width:
1.875 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.875 inches
Center To Center Distance Between Terminals Parallel To Width:
0.625 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.780 inches
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
Thd bushing
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
1.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
300.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic-hydraulic all locations
Trip Release Characteristic:

Time delay all locations

## NSN 5925-01-028-2782

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.500 at 100 pct all locations and 9.000 at 125 pct all locations
Inclosure Protection Type For Which Designed:
Dustproof and explosion resistant and fungus resistant and moisture resistant and shockproof and vibrationproof
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unef
Terminal Type And Quantity:
5 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0