Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-031-9915

## **Thread Pitch Diameters:**

+0.3503/+0.3537 inches

#### **Body Style:**

Single pole type

#### **Bushing Length:**

0.330 inches

#### **Body Length:**

1.562 inches

#### **Body Width:**

0.625 inches

#### **Case Material:**

Metal

#### Center To Center Distance Between Terminals Parallel To Length:

0.910 inches

#### Fragility Factor:

Moderately rugged

## Mounting Surface To Terminal End Distance:

1.700 inches

#### **Pole Quantity:**

1

#### Arc Quenching Method:

Magnetic blowout

#### Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

#### Storage Type:

General purpose warehouse

#### Thready Qty Per Inch (tpi):

32

#### Maximum Continuous Load Current Rating Per Pole:

25.0 amperes dc single location

#### **Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc single location

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 dc single location

## Circuit Protection Type:

Overcurrent single location

## Trip Release Method:

Magnetic single location

## Trip Release Characteristic:

Time delay single location

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 single location

# NSN 5925-01-031-9915

Circuit Breaker - Page 2 of 2



Reset Method:	
Manual	
Main Contact Tripp	ing Mechanism Type:
Trip free	
Manual Actuator T	ype And Quantity:
1 toggle	
Actuator Function	
Trip-reset	
Actuator Position	Designation:
At pole one	
Internal Trip Relea	se Configuration:
Series trip single loc	ation
Thread Size:	
0.375 inches	
Trip Delay Time In	Seconds Per Rated Continuous Current:
0.080 at 200 pct sir	gle location and 0.700 at 200 pct single location
Inclosure Protection	n Type For Which Designed:
Fungus resistant	
Unpackaged Unit V	Veight:
2.100 ounces	
Test Data Docume	nt:
13973-860028-43 d	awing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any s	pecification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Des	gnator:
Unef	
Terminal Type And	Quantity:
2 wire hook	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A030a0	