

View Online at <https://aerobasegroup.com/nsn/5925-01-032-1123>

**Thread Pitch Diameters:**

+0.1177/+0.1214 inches

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.530 inches

**Body Width:**

Between 2.205 inches and 2.285 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.660 inches and 1.960 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.046 inches and 2.078 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.140 inches

**Mounting Surface To Terminal End Distance:**

2.800 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

6 threaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.150 at 200 pct all locations and 1.900 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant

Switch Terminal Type:

Knife blade

Switch Current Rating And Type In Amps:

10.0 ac and 2.0 dc

Switch Voltage Rating And Type In Volts:

250.0 ac and 50.0 dc

Frequency In Hertz:

400.0 all locations

Test Data Document:

81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Specification Data:**

81349-mil-c-55629/6 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0