

View Online at <https://aerobasegroup.com/nsn/5925-01-033-7887>

Body Style:

Multipole-single actuator type

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.190 inches

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

150.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip w/separate reset

Trip Delay Time In Seconds Per Rated Continuous Current:

100.000 at 200 pct all locations and 300.000 at 200 pct all locations and 50.000 at 250 pct all locations and 140.000 at 250 pct all locations and 30.000 at 300 pct all locations and 80.000 at 300 pct all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 screw base

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0