## NSN 5925-01-034-7501



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-034-7501 **Body Style:** Multipole-single actuator type **Bushing Length:** 0.675 inches **Body Length:** 1.562 inches **Body Width:** 1.875 inches **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** 0.875 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.625 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.780 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** Thd bushing Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations **Circuit Protection Type:** Overcurrent all locations

**Trip Release Method:** 

Magnetic-hydraulic all locations

**Trip Release Characteristic:** 

Time delay all locations

## NSN 5925-01-034-7501

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.500 at 100 pct all locations and 9.000 at 125 pct all locations
Inclosure Protection Type For Which Designed:
Dustproof and explosion resistant and fungus resistant and moisture resistant and shockproof and vibrationproof
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0