## NSN 5925-01-039-3071



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-039-3071 **Body Style:** Multipole-single actuator type **Body Length:** 10.125 inches **Body Width:** 8.125 inches **Body Height:** 3.812 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 7.749 inches **Center To Center Distance Between Terminals Parallel To Width:** 2.750 inches **Unthreaded Mounting Hole Diameter:** 0.190 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: **7.749** inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Fragility Factor:** Moderately rugged **Boss Height:** 1.688 inches **Pole Quantity:** 3 **Arc Quenching Method: Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 600.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations

**Circuit Protection Type:** 

Overcurrent all locations

**Trip Release Method:** 

Thermal-magnetic all locations

## **NSN 5925-01-039-3071** Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Trip Release Ambient Tempurature Rating:
35.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A030a0