## NSN 5925-01-040-8724

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-040-8724 **Body Style:** Single pole type **Body Length:** 6.000 inches **Body Width:** 2.750 inches **Body Height:** 3.375 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: **4.719 inches Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 50.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

**Actuator Function:** 

Trip-reset

## **NSN 5925-01-040-8724** Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole one
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
240.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0