NSN 5925-01-043-9978

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-043-9978

Body Style:
Multipole-single actuator type
Body Length:
6.000 inches
Body Width:
4.344 inches
Body Height:
3.000 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
5.125 inches
Center To Center Distance Between Terminals Parallel To Width:
1.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
5.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.500 inches
Boss Height:
0.125 inches
Pole Quantity:
3
3 Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded hole
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi):
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole:
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts:
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations and 250.0 dc all locations
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations and 500.0 dc all locations
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations and 500.0 dc all locations Circuit Protection Type:
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations and 500.0 dc all locations Circuit Protection Type: Overcurrent all locations
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations and 500.0 dc all locations Circuit Protection Type: Overcurrent all locations Trip Release Method:
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations and 500.0 dc all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Thermal-magnetic all locations
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations and 500.0 dc all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Thermal-magnetic all locations Trip Release Characteristic:
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations and 500.0 dc all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Thermal-magnetic all locations Trip Release Characteristic: Time delay all locations
Mounting Facility Type And Quantity: 4 threaded hole Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac all locations and 20.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations and 500.0 dc all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Thermal-magnetic all locations Trip Release Characteristic: Time delay all locations Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

NSN 5925-01-043-9978 Circuit Breaker - Page 2 of 2

