

View Online at <https://aerobasegroup.com/nsn/5925-01-045-2119>

Body Style:

Multipole-single actuator type

Bushing Length:

0.250 inches

Body Length:

2.000 inches

Body Width:

0.850 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.800 inches

Center To Center Distance Between Terminals Parallel To Width:

0.500 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

2.765 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

Thd bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

750.0 milliamperes ac all locations and 750.0 milliamperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations and 28.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 ac all locations and 2000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct all locations and 35.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0