# NSN 5925-01-045-9602

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-045-9602

#### **Body Style:**

Multipole-single actuator type

### **Body Length:**

3.000 inches

# Body Width:

2.090 inches

#### **Body Height:**

2.580 inches

#### **Case Material:**

Plastic

# Center To Center Distance Between Terminals Parallel To Width:

0.740 inches

#### **Boss Height:**

0.250 inches

# **Pole Quantity:**

3

# Mounting Facility Type And Quantity:

6 terminal

# Maximum Continuous Load Current Rating Per Pole:

40.0 amperes ac all locations

# **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Magnetic all locations

#### **Trip Release Characteristic:**

Time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

# Manual Actuator Type And Quantity:

1 toggle

# **Actuator Function:**

Trip-reset

### Actuator Position Designation:

At pole two

# NSN 5925-01-045-9602

Circuit Breaker - Page 2 of 2



# Internal Trip Release Configuration:

Series trip all locations

# Trip Delay Time In Seconds Per Rated Continuous Current:

240.000 at 200 pct all locations

# Frequency In Hertz:

60.0 all locations

# Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0