

View Online at <https://aerobasegroup.com/nsn/5925-01-046-3751>

Thread Pitch Diameters:

+0.1177/+0.1214 inches

Body Style:

Multipole-multiple actuator type

Body Length:

2.510 inches

Body Width:

2.245 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.810 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

2.553 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct all locations and 9.450 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Moisture resistant

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0