## NSN 5925-01-046-7448

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-046-7448

Body Style:
Multipole-multiple actuator type
Body Length:
5.125 inches
Body Width:
3.108 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
3.550 inches
Center To Center Distance Between Terminals Parallel To Width:
1.026 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length
2.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.026 inches
Boss Height:
0.220 inches
Mounting Surface To Terminal End Distance:
3.360 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
6 threaded hole
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
70.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
208.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
5000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
100.0 all locations
Reset Method:

Manual

## **NSN 5925-01-046-7448** Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
3.000 at 200 pct all locations and 10.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0