NSN 5925-01-048-7914

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-048-7914

Body Style: Single pole type

Body Length: 2.530 inches

Body Width:

0.760 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.800 inches and 1.820 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

2.690 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

NSN 5925-01-048-7914

Circuit Breaker - Page 2 of 2



| Manual Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 toggle Actuator Function: Trip-reset Actuator Position Designation: At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material And Location: Contact surfaces silver Precious Material Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A030a0 | Reset Method: |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Trip free Manual Actuator Type And Quantity: 1 toggle Actuator Function: Trip-reset Actuator Position Designation: At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: | Manual |
| Manual Actuator Type And Quantity: 1 toggle Actuator Function: Trip-reset Actuator Position Designation: At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Main Contact Tripping Mechanism Type: |
| 1 toggle Actuator Function: Trip-reset Actuator Position Designation: At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig: | Trip free |
| Actuator Function: Trip-reset Actuator Position Designation: At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: | Manual Actuator Type And Quantity: |
| Trip-reset Actuator Position Designation: At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 1 toggle |
| Actuator Position Designation: At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Actuator Function: |
| At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Trip-reset |
| Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Actuator Position Designation: |
| Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: | At pole one |
| Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig: | Internal Trip Release Configuration: |
| O.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: | Series trip single location |
| Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: | Thread Size: |
| 3.000 at 200 pct single location and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 0.138 inches |
| Inclosure Protection Type For Which Designed: Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: | Trip Delay Time In Seconds Per Rated Continuous Current: |
| Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 3.000 at 200 pct single location and 10.000 at 200 pct single location |
| Frequency In Hertz: 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Inclosure Protection Type For Which Designed: |
| 60.0 single location Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Explosion proof and vibrationproof and shock resistant and fungus resistant and moisture resistant |
| Unpackaged Unit Weight: 0.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Frequency In Hertz: |
| O.312 pounds Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 60.0 single location |
| Precious Material And Location: Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Unpackaged Unit Weight: |
| Contact surfaces silver Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 0.312 pounds |
| Precious Material: Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Precious Material And Location: |
| Silver Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Contact surfaces silver |
| Thread Series Designator: Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Precious Material: |
| Unc Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Silver |
| Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Thread Series Designator: |
| 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Unc |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Terminal Type And Quantity: |
| N/a Unit Of Measure: Demilitarization: No Fiig: | 2 threaded stud |
| Unit Of Measure: Demilitarization: No Fiig: | Shelf Life: |
| Demilitarization: No Fiig: | N/a |
| No Fiig: | Unit Of Measure: |
| No Fiig: | |
| Fiig: | Demilitarization: |
| - | No |
| A030a0 | Fiig: |
| | A030a0 |
| | |