## NSN 5925-01-049-3178

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-049-3178

**Body Style:** 

Single pole type

**Bushing Length:** 

Between 0.219 inches and 0.281 inches

**Body Length:** 

Between 0.719 inches and 0.781 inches

**Body Width:** 

Between 0.531 inches and 0.593 inches

Case Material:

**Plastic** 

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 0.672 inches and 0.734 inches

**Fragility Factor:** 

Moderately rugged

**Mounting Surface To Terminal End Distance:** 

Between 1.919 inches and 1.981 inches

**Pole Quantity:** 

1

**Arc Quenching Method:** 

Air

**Mounting Facility Type And Quantity:** 

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

**Maximum Continuous Load Current Rating Per Pole:** 

1.0 amperes ac single location and 1.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:** 

200.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location and 5000.0 dc single location

**Circuit Protection Type:** 

Overcurrent single location

Trip Release Method:

Thermal single location

**Trip Release Characteristic:** 

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

120.0 single location

**Reset Method:** 

Manual

## **NSN 5925-01-049-3178** Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.469 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct single location and 20.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Vibrationproof and fungus resistant and moisture resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
38.0 grams
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0