## NSN 5925-01-049-3952

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-049-3952

Body Style:
Multipole-multiple actuator type
Body Length:
2.000 inches
Body Width:
1.500 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.560 inches
Center To Center Distance Between Terminals Parallel To Width:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.660 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Boss Height:
0.130 inches
Mounting Surface To Terminal End Distance:
1.880 inches
Pole Quantity:
2
Mounting Facility Type And Quantity:
A descended by the
4 threaded hole
Storage Type:
Storage Type:
Storage Type: General purpose warehouse
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi):
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole:
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes ac second location
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes ac second location Operating Voltage Type And Rating Per Pole In Volts:
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes ac second location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes ac second location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes ac second location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes ac second location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations Circuit Protection Type:
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes ac second location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations Circuit Protection Type: Overcurrent all locations
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes ac second location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method:
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes ac second location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes ac second location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Trip Release Characteristic:

## **NSN 5925-01-049-3952** Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.200 at 200 pct all locations and 20.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
5.000 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0