## NSN 5925-01-051-3265



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-051-3265 **Body Style:** Multipole-single actuator type **Body Length:** 2.891 inches **Body Width:** 2.000 inches **Body Height:** 2.375 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Boss Height:** 0.187 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 terminal **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

**Actuator Position Designation:** 

At pole one

## NSN 5925-01-051-3265

Circuit Breaker - Page 2 of 2



| Trin | Delay | Time   | In s | Seconds        | Per | Rated | <b>Continuous</b> | Current: |
|------|-------|--------|------|----------------|-----|-------|-------------------|----------|
| HID  | Delay | 111116 | ш,   | <b>Jeconus</b> | ГСІ | naieu | Continuous        | Current. |

120.000 at 200 pct all locations

**Trip Release Ambient Tempurature Rating:** 

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

**Terminal Type And Quantity:** 

2 clip and 2 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0