

View Online at <https://aerobasegroup.com/nsn/5925-01-056-7608>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

Between 2.437 inches and 2.563 inches

**Body Width:**

Between 2.187 inches and 2.313 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 2.000 inches and 2.127 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.687 inches and 0.813 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.000 inches and 2.127 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.687 inches and 0.813 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.062 inches and 0.188 inches

**Mounting Surface To Terminal End Distance:**

Between 2.375 inches and 2.501 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

6 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

40.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

150.0 ac third location

**Trip Release Characteristic:**

Time delay first location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series/relay trip third location

**Thread Size:**

0.138 inches

**Trip Release Duty Cycle:**

Continuous third location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.000 at 200 pct all locations and 20.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

General purpose

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Unpackaged Unit Weight:**

10.000 ounces

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

8 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0