NSN 5925-01-057-1455

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-057-1455

Body Style:
Single pole type
Mounting Slot Width:
0.178 inches
Body Length:
Between 5.790 inches and 5.810 inches
Body Width:
Between 1.016 inches and 1.036 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
Between 3.537 inches and 3.557 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 2.740 inches and 2.760 inches
Fragility Factor:
Moderately rugged
Boss Height:
Between 0.209 inches and 0.229 inches
Mounting Surface To Terminal End Distance:
Between 2.599 inches and 2.619 inches
Pole Quantity:
1
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
2 threaded hole
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
5.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
5000.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic-hydraulic single location
Trip Release Characteristic: Time delay single location

NSN 5925-01-057-1455

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

40.000 at 200 pct single location and 125.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

60.0 single location

Unpackaged Unit Weight:

1.770 pounds

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0