NSN 5925-01-057-6046

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-057-6046

Body Style:

Multipole-single actuator type

Body Length:

10.500 inches

Body Width:

4.125 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

8.875 inches

Center To Center Distance Between Terminals Parallel To Width:

1.719 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.438 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.719 inches

Boss Height:

0.500 inches

Mounting Surface To Terminal End Distance:

13.781 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

400.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

NSN 5925-01-057-6046 Circuit Breaker - Page 2 of 2



N	lanual
M	lain Contact Tripping Mechanism Type:
	rip free
M	lanual Actuator Type And Quantity:
1	toggle
A	ctuator Function:
т	rip-reset
A	ctuator Position Designation:
A	t pole two
т	rip Delay Time In Seconds Per Rated Continuous Current:
9	0.000 at 200 pct all locations and 550.000 at 200 pct all locations
Ir	closure Protection Type For Which Designed:
F	ungus resistant and moisture resistant
Т	rip Release Ambient Tempurature Rating:
4	0.0 degrees celsius all locations
F	requency In Hertz:
6	0.0 all locations
Т	erminal Type And Quantity:
6	threaded stud
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
N	0
F	iig:
A	030a0